

Cover Models





2 pound High Density Foam Fiber Board with 250°F Surface Temperature Resistance 2" Heavy Duty Aluminum Channel 4" to 2" Super Taper 2 pound density Polystyrene Foam Core

Spa Seal 1000

- 28 Ounce Marine Grade vinyl available in 10 colors. (Jade, Burgundy, Navy Blue and Black not available)
- 12 oz mildew and chemical resistant double laminated bottom fabric.
- 1 1/2 pound solid polystyrene core (EPS).
- 2" Heavy Duty Aluminum channeling. No corrosion, strong and lightweight.
- · Three year warranty for defects in material or manufacturing.

Spa Seal 2000

- · UL Approved Safety Cover.
- 28 Ounce Marine Grade vinyl available in 14 colors.
- 16 oz mildew and chemical resistant double laminated bottom fabric. Laminated Core. Best core available for surface temperature resistance
- and rigidity to reduce foam degradation and water pooling.
- One inch thick high density rigid foam fiber board with 250° F surface temperature resistance
- Backed with one pound polystyrene foam for insulation and light weight
- 2" Heavy Duty Aluminum channeling. No corrosion, strong and lightweight.
- Five year warranty for defects in material or manufacturing.

Spa Seal 3000

- · UL Approved Safety Cover.
- 28 Ounce Marine Grade vinvl available in 14 colors.
- High Density Laminated Core. Best core available for surface temperature resistance, superior strength and rigidity to reduce foam degradation and water pooling. Two layers of two pound foam provides the highest possible strength for heavy snow and commercial applications. This is our strongest core.
- One inch thick high density rigid foam fiber board with 250° F surface temperature resistance

16 oz mildew and chemical resistant double laminated bottom fabric.

- Backed with two pound polystyrene foam for insulation and superior strength.
- 2" Heavy Duty Aluminum channeling. No corrosion, strong and lightweight.
- · Five year warranty for defects in material or manufacturing.