



## Drains & Suctions / SPC-3 V & SPC-3M V - 5" Super Hi-Flo Suctions

### FEATURES:

- New Super Hi-Flo rating of 180 GPM
- Self-Contained Spa rating of 251 GPM
- Available in 2" and 2 1/2" S sizes
- 2 1/2" can be used with vacuum break fittings (below) for an extra high rating of 232 GPM (non-Stainless Steel ONLY!)

### SPECIFICATIONS:



- Total Open Area: 9.02 sq. in.
- Floor Flow Rate: N/A
- Wall Flow Rate: 180 GPM @ 6.42 ft/sec
- Flow Rate @ 1.5 ft/sec: 42 GPM



640-3580S V



640-3577 V



### SPC-3 V & SPC-3M V - 5" Hi-Flo Suctions

Part No.	Description	Case Quantity	List (US \$)
640-357x V	Super Hi-Flo Suction Assembly - 2" S	35	22.07
640-3570S V	Super Hi-Flo Suction Assembly - 2" S - Stainless Steel	40	32.40
640-358x V	Super Hi-Flo Suction Assembly - 2 1/2" S	40	22.07
640-3580S V	Super Hi-Flo Suction Assembly - 2 1/2" S - Stainless Steel	40	32.40

Replace the final x in the part number with the color of your choice (see page iv for colors).



643-3610 V



642-3700 V



413-2330 V



642-3680 V



640-3750 V



642-3680



642-3700

### FEATURES:

- For 2 1/2" Super Hi-Flo Suctions (non-stainless steel) only
- Improves performance and safety
- Available in four different plumbing configurations
- Increases UL Approved flow rating to 232 GPM

### Vacuum Break Fittings for 2 1/2" SPC-3 V Suctions

Part No.	Description	Case Qty.	List (US \$)
413-2330 V	2" Vacuum Break Suction Tee	30	5.95
642-3610 V	2 1/2" S Vacuum Break 90° Ell	40	5.10
642-3700 V	2" S Vacuum Break 90° Ell	50	4.93
642-3680 V	2" Straight Vacuum Break	70	4.93
640-3750 V	3/4" SB Suction Vent	50	8.78

### Non-Vacuum Break Fittings for 2 1/2" SPC-3 V Suctions

Part No.	Description	Case Qty.	List (US \$)
642-3680	2 1/2" x 2" S Straight Adapter	80	5.80
642-3700	2 1/2" x 2" S 90° Ell Adapter	55	5.80