

# TESTED. TRUSTED. PROVEN TECHNOLOGY. WATERWAY SUPER HI-FLO SUCTIONS.

640-358x V



640-357x V Super Hi-Flo Suction Assembly - 2" S  
640-358x V Super Hi-Flo Suction Assembly - 2 1/2" S

## 5" 180 GPM Super Hi-Flo Suction Assembly

### FEATURES:

- Complies with VGB 2008 and is UL tested to meet the requirements of ASME A112.19.8-2007
- New Super Hi-Flo rating of 180 GPM
- Available in 2" S and 2 1/2" S sizes
- Can be used with vacuum break fittings (below) for an extra high rating of 232 GPM

## Vacuum Break Fittings (Increase flow rating to 232 GPM)

In case of obstruction of suction fitting openings, the differential pressure causes air to be pulled into the pump suction line. As a result, the pump will lose prime and breaks the vacuum behind the suction cover. The Waterway Super Hi Flo Spa Suction with Vacuum Break is easy to install and service.

### FEATURES:

- Improves performance and safety
- Complies with VGB 2008 and is UL tested to meet the requirements of ASME A112.19.8-2007
- Increases UL Approved flow rating to 232 GPM
- Available in four different plumbing configurations



642-3700 V

640-3750 V

642-3680 V

642-3610 V

413-2330 V

413-2330 V 2" Vacuum Break Suction Tee  
642-3610 V 2 1/2" S Vacuum Break 90° El  
642-3700 V 2" S Vacuum Break 90° El  
642-3680 V 2" Straight Vacuum Break  
640-3750 V 3/4" SB Suction Vent



**Waterway**™

Be Sure it's  
Genuine

