

System:2™ Mod Media™ Filters — PLM Series by Sta-Rite®



Greater dirt-loading capacity reduces maintenance

The System:2 Mod Media filter is ideal for small inground and aboveground pools. This filter is a compact adaptation of System:3® technology from Sta-Rite, so it handles dirt loads up to 15 times greater than sand filters of equivalent size. The result: you capture more dirt between cleanings and minimize time on maintenance.

- Rugged composite construction resists corrosion and weathering.
- Compact design fits easily in tight installations and can be easily shielded from view.
- Balanced-flow tank design works in unison with the high capacity filter module to collect dirt over its entire surface—holds more dirt so you clean less often.
- Less frequent cleaning also increases filter module service life and lowers lifetime costs.



System:2™ Mod Media™ Filters — PLM Series



Top-mounted pressure gauge and information panels are positioned for easy reading

Split-tank design permits simple, thorough rinse-in-place cleaning to save time

Posi-Ring® closure is easy to secure, lasts for years

Balanced-flow tank hydraulics direct water through each side of the filter module for uniform dirt loading to prevent clogging and maximize filtration effectiveness



Easy to clean — just spray and go



The Mod Media filter contains a one-piece module that simply drops into an easily accessible tank. When cleaning is necessary, just remove the lid (no tools are necessary) and spray-rinse the module while it is still in place.* It only takes minutes to thoroughly clean the filter and get back into service — fast.



Less maintenance . . . YES!

The balanced-flow tank design directs water through both sides of the filter module which increases dirt-loading without clogging. Holding more dirt means a longer time between cleanings.

*Modules used in conjunction with certain pool/spa sanitizers may require soaking in special cleaning solutions

System Performance

Model	For Pools up to (Gal.) 8 Hr. Turnover	Filter Area (Sq. Ft.)	Flow Rate ¹ (GPM)
PLM100	48,000	100	38-100
PLM125	60,000	125	47-125
PLM150	72,000	150	56-150
PLM175	72,000	175	66-150
PLM200	72,000	200	75-150
PLM300	72,000	300	113-150

¹Based on NSF recommended flow rate for commercial at .375 GPM per square foot

Operating Limits — Maximum continual operating pressure is 50 psi. For pool/spa (bather) applications, the maximum operating water temperature within the filter is 104°F (40°C)

One-year limited warranty. See warranty for details.

Available from:



Simply Smarter.

www.staritepool.com

Phone: 800-831-7133



pumps / filters / heaters / heat pumps / automation / lighting / cleaners / sanitizers / water features / maintenance products

All Pentair trademarks and logos are owned by Pentair, Inc. Sta-Rite®, System:3®, System:2™, Mod Media™ and Posi-Ring® are trademarks and/or registered trademarks of Pentair Water Pool and Spa, Inc. and/or its affiliated companies in the United States and/or other countries. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.