



## *Easy, Elegant Design Fits Your Lifestyle*

Our LT heaters are powerful, efficient and easy to operate. And inside the incredibly reliable LT heaters, you'll find plenty of features to warm up to:

- ▶ Automatic pool-to-spa switching
- ▶ Fan-assisted controlled combustion for consistent efficiency—up to 83%
- ▶ Corrosion resistant polymer headers for long term reliability
- ▶ Meets all air quality standards (Low NOx)
- ▶ Contemporary design blends into any backyard landscape

### POOL-TO-SPA SWITCHING



The LT heater is automation ready with convenient pool to spa switching, eliminating the drudgery of manually turning valves to operate the spa.

### DUAL ELECTRONIC THERMOSTAT



Dual set points provide convenient pool and spa temperature settings. LED indicators give easy to understand diagnostic information.

### REMOTE CONTROL



With the addition of the EZ Wireless Remote Control, you can operate pool and spa functions without trips to the equipment area.



# Powerful, Efficient and Automation-Ready

## LT Heaters



### Convenient Controls

and dual electronic thermostat are key elements in your AquaLink® RS controlled pool and spa environment. The LT includes automation-ready features to provide convenient pool-to-spa switching.



### LT PERFORMANCE CHARTS

The Pool Sizing Guide below shows the maximum pool surface area LT models 250 and 400 will heat based on the Temperature Difference\* between the air temperature during the coldest month the pool is used and the desired pool temperature. Figures are based on average wind conditions and average pool depth.

#### POOL SIZING GUIDE

Model	250		400	
Temp Difference*	Maximum Area Heater (width x length)			
	0 Wind	3 1/2 MPH	0 Wind	3 1/2 MPH
15°F	1750	1300	2800	2100
20°F	1300	1000	2100	1600
25°F	1050	800	1700	1280
30°F	850	650	1400	1050
35°F	750	570	1200	900

The Spa Sizing Guide below details the time required for each model to raise spa temperature by 30°F.

#### SPA SIZING GUIDE

Model	250	400
Spa Size	Time Required to Raise Temp 30°	
200 Gallons	15 Minutes	10 Minutes
400 Gallons	30 Minutes	20 Minutes
600 Gallons	45 Minutes	30 Minutes
800 Gallons	60 Minutes	45 Minutes
1000 Gallons	75 Minutes	50 Minutes

### Specifications:

Model	"A" Width	Height	Depth	VENT	Shipping Weight	Heater Weight
250	28 1/4"	30 7/8"	27 1/8"	7.0"	237 lbs.	170 lbs.
400	34 1/4"	30 7/8"	27 1/8"	9.0"	308 lbs.	236 lbs.

  

*See your Jandy Sales Representative for more information!*



**ALL JANDY PRODUCTS WORK SEAMLESSLY TOGETHER**

Jandy Control Systems manage our complete line of technologically advanced products.



Pumps • Filters • Heaters • Air Energy Heat Pumps  
Controls • Lights • Water Purification Systems • Valves  
Water Features • Cleaners • Accessories

